

# MSI-9750A CellScale™ RF Portable Indicator



## Standard Features

- Compatible with MSI-6260CS, MSI-9300 and MSI-9000 CellScale
- 1.4 in x 2.6 in (36 mm x 67 mm), eight line, 21 character LCD display
- 2.4 GHz spread spectrum transceiver
- Power supply: six cell NiMH battery pack
- Charger board: SMD NiMH fast charge (charges battery pack in two hours or less)
- RS-232 data I/O
- Real-time clock
- NEMA Type 3, IP55 enclosure
- AC adaptor/battery charger; 90-264 VAC, 47-63 Hz (NA plug standard)

## Approvals



## Part Number/Price

Part #	MSI Part #	Description	Est. Weight	Price
138486	502541-0001	MSI-9750 RF portable indicator	2.2 lb (1 kg)	Consult

## Options/Accessories

Part #	MSI Part #	Description	Est. Weight	Price
<b>Accessories</b>				
143709	12431	Replacement NiMH battery pack	1 lb (0.45 kg)	Consult
139484	503441-0001	AC adaptor/battery charger input, 90-264 VAC, 47-63 Hz (NA plug standard)	1 lb (0.45 kg)	Consult
143912	12674	Battery charger, 12 VDC auto plug	1 lb (0.45 kg)	Consult
139485	503441-0002	AC adaptor/battery charger, EU plug	1 lb (0.45 kg)	Consult

## Specifications

### Enclosure:

NEMA Type 3, IP54, Rugged Molded PVC, O-ring gasketed.

### Dimensions:

4.6in x 10.3in x 2.4 in (117 x 262 x 60.5 mm)

### Weight:

2.2 lb (1 kg)

### Keypad:

24 keys—11 key alphanumeric, 7 control keys and 6 user programmable keys.  
Password protected with lock feature

### Display:

1.4in x 2.6in (36 x 67 mm) backlight LCD capable of 8 lines, 21 characters each. Backlight selectable On, Off or Automatic. Red/Green LED battery charging indicator

### Power:

Rechargeable 6 cell NiMH battery pack (AC Adapter/Battery Charger Input Included)

### Operating Time:

Up to 8 hours typical use. Selectable automatic shut off for battery conservation

### Operating Temperature:

-4° to 158°F (-20° to 70°C)

### Radio Link:

FHSS at 2.4 GHz (Up to 64 network selections)

### Radio Effective Range:

Typically 500 ft (150 m) indoors, 1000 ft (300 m) outdoors with standard antennas

### RFI/EMI Shielding:

Exceeds NIST HB44 and CE Standards

### Connectors:

Charger Input: Standard 2.5 mm coaxial; RS-232: Standard DB-9 male

### Warranty:

One-year limited

### Approvals:

NTEP CC 05-077