MINEBEA INTEC Midrics Series

Complete Scale



Specifications

Indicators:

MIS1 - UR 20 mm LCD

Power Supply: 100 - 200 VAC, 50 - 60 Hz

Readability:

15,000 scale intervals

Cable Length:

2.5 m

Warranty:

Two-year limited warranty

Standard Features

- · Capacities from 6 kg to 60 kg
- Painted versions have IP65 protection rating for industrial use
- 304 Stainless steel versions have IP67/IP68 protection ratings
- Four adjustable feet, level indicator on LCE and NCE
- 10 ft cable platform
- Midrics 1 display, for simple weighing tasks
- Midrics 2 with 10-key touchpad and application programs
- Midrics 2 application programs counting, checkweighing, classification, totalizing, net-total formulation, animal weighing, percent weighing, neutral measurement
- Optional accessories: User-installed interface kits, printer, external battery pack, software tools, panel mount kit


Part Number/Price

RLWS PN	Minebea PN	Dimensions	# Load Cells	Capacity Re	eadability	Est. Weight	Price
103668	MW1P1U-6DC-L	12.5 x 9.5 in	1	6 kg	0.5 g	22 lb	Consult
103669	MW1P1U-15DC-L	12.5 x 9.5 in	1	15 kg	1g	24 lb	Consult
103670	MW1P1U-30ED-L	15.75 x 11.8 in	1	30 kg	2 g	24 lb	Consult
103671	MW1P1U-60ED-L	15.75 x 11.8 in	1	60 kg	5 g	24 lb	Consult
103672	MW1P1U-60FE-L	19.5 x 15.75 in	1	60 kg	5 g	22 lb	Consult

Options/Accessories

RLWS PN	Minebea PN	Description	Price
171727	YDH12CWSUS	Holder base mount for ED base	Consult
Consult	Consult	Stainless steel column	Consult
105607	YDH02CISUS	Wall-mount bracket, SST, tiltable	Consult
193048	YDC01SW	Indicator dust cover pack of two	Consult
Consult	YBP03CIS	Base for installing floor mounted option, SST	Consult
Consult	YAS03MI	Indicator panel mount option	Consult

Custom Part No. Configuration



Capacities	Platform Sizes
6 kg x 0.5 g	$DC = 12.5 \times 9.5 \text{ in}$
15 kg x 1 g	ED = 15.75 x 11.8 in
30 kg x 2 g	FE = 19.5 x 15.75 in
60 ka x 5 a	