NEW RoughDeck® Rough-n-Ready System

Floor Scale and 380 Indicator Package



Standard Features

- Package includes: RoughDeck HP 4 ft x 4 ft x 3.5 in floor scale, 20 ft of hostile environment load cell cable, quick disconnect and 380 indicator
- Package is factory-calibrated for 5,000 divisions


- Heavy-duty design with structural steel under support
- Four NTEP certified alloy steel shear beam load cells
- Side-access JB4SS TuffSeal® junction box

Indicator:

- · LCD display
- Two independent serial ports, RS-232 and USB 2.0

Approvals











RoughDeck Specifications

End Load Capacity:

100% full scale at 5,000 lb 80% full scale at 10,000 lb

Cable Length:

20 ft (6.1m) for connecting junction box to indicator

Threaded Eyebolt:

Hole (1/2-20 NF) located in center of deck for easy lifting

Warranty (limited):

RoughDeck HP weldment five years, load cells two years, all other components one year

Approvals:

NTEP CC 92-001, Class III 5,000d Measurement Canada AM-4827, Class III 5,000d

380 Specifications

Power:

Batteries: 4 Alkaline C-cell

Optional: 115/230 VAC to 12 VDC adapter

Batteru Life:

45 hours continuous use, on Alkaline batteries with four 350 ohm load cells, low backlight

Communication Ports:

One RS-232 (three-wire) One USB 2.0

Display:

Six 1 in (25 mm) tall, LCD digits

g, lb, t, tn, kg, oz, battery level, PT, LT, gross, zero, unstable, net

5 tactile buttons

Rating/Material: Enclosure: IP66, 304 stainless steel

Approvals:

NTEP CC 21-051 Measurement Canada AM-5892 CE Marked **UL/cUL** Listed

RoughDeck® Rough-n-Ready System Floor Scale and 380 Indicator Package

Part Number/Price

Part#	Floor Scale Capacity	Indicator	Est. Weight	Price	
[†] 4ft x 4ft x 3.5 in RoughDeck (NTEP Certified) Indicator Package with Tilt Stand					
208558	5,000 lb	380	405 lb	Consult	
208585	10,000 lb	380	405 lb	Consult	
⁺ 4ft x 4ft x 3.5 in RoughDeck (Canadian Weights and Measures Approved) Indicator Package with Tilt Stand					
208582	2,500 kg	380	405 lb	Consult	
208586	5,000 kg	380	405 lb	Consult	

Options/Accessories

Part#	Description	Price
206433	External AC adapter for 380 indicator	Consult
Consult	Access ramps available	See catalog page 383
Consult	Pit frames available	See catalog page 385
Consult	Bumper guards available	See catalog page 388 through catalog page 390
Consult	Portability frames available	See catalog page 391 through catalog page 394
18777	Floor anchor plates, mild steel (set of 2)	Consult
19352	RoughDeck floor stand for indicator, 36.3 in high, mild steel	Consult
126384	RoughDeck floor stand for indicator, 48 in high, mild steel	Consult



† US plug (NA) - Type A