

Summit® Scale and Indicator Package

Floor Scale/120 Indicator Package

FLOOR SCALES



Package is configured, corner-trimmed and calibrated for 5,000 divisions before shipping

Floor Scale and Indicator Package

Package includes Summit® 3000 floor scale, 120 digital weight indicator with tilt stand, 20ft load cell cable with quick disconnect; configured and calibrated

Standard Features

Summit® 3000 Floor Scale

- Four NTEP Certified alloy steel-shear beam load cells
- Top access junction box
- Rugged diamond safety treadplate steel deck
- Four adjustable rigid polyurethane rubber feet, 3 in (76.2 mm) diameter
- Signal trim summing board housed in ABS enclosure
- Threaded eyebolt hole (1/2–20NF) located in the center of the deck for easy lifting
- 20 ft of EL147 load cell cable with quick disconnect
- Package configured and calibrated for 5,000 divisions
- Factory-calibrated for 5,000 divisions

120 Digital Weight Indicator

- Large 0.8 in (20.3 mm) light emitting diode (LED) display
- Five-button operation
- Full front panel digital calibration and configuration

Summit 3000 Floor Scale Specifications

End Load Capacity:

- 100% full scale at 5,000 lb (2,500 kg)
- 80% full scale at 10,000 lb (5,000 kg)

Cable Length:

- 20 ft (6.1 m) (for connecting junction box to indicator)

Warranty:

- Summit 3000 weldment and load cells two years, all other components one year

Approvals:

- NTEP CC 92-001A9, Class III 5,000 d
- Measurement Canada AM-5530, Class III 5,000 d

120 Plus Digital Weight Indicator Specifications

Power:

- Line voltages: 115 or 230 VAC
- Frequency: 50 or 60 Hz

Operating Temperature:

- Legal: 14° F to 104° F (-10° C to 40° C)
- Industrial: 14° F to 122° F (-10° C to 50° C)

Rating/Material:

- Enclosure: heavy gauge ABS

Warranty:

- One-year limited warranty

Approvals:

- NTEP CC 03-059, Class III/IIIL 6,000 d
- Measurement Canada AM-5517, Class III/IIILD 6,000 d
- 6,000 d OIML TC7028 T 5692, 5,000 d
- CE marked

Approvals



www.ricelake.com | Phone: 800-472-6703

RICE LAKE

Summit[®] Scale and Indicator Package

Floor Scale/Indicator Package

Part Number/Price

Part #	Size (W x L x H)	Capacity	Est. Weight	Price
Floor Scale and Indicator Package (Single Scale)				
Package includes Summit [®] 3000 floor scale, 120 digital weight indicator with tilt stand, 20 ft load cell cable with quick disconnect; configured and calibrated				
115 VAC				
78772	4 ft x 4 ft x 3.625 in	5,000 lb x 1 lb	315 lb	Consult
78773	4 ft x 4 ft x 3.625 in	10,000 lb x 2 lb	315 lb	Consult
230 VAC				
78780	4 ft x 4 ft x 3.625 in	5,000 lb x 1 lb	315 lb	Consult
78781	4 ft x 4 ft x 3.625 in	10,000 lb x 2 lb	315 lb	Consult
115 VAC Measurement Canada Approved				
78776	4 ft x 4 ft x 3.625 in	2,500 lb x 0.5 kg	315 lb	Consult
78777	4 ft x 4 ft x 3.625 in	5,000 lb x 1 kg	315 lb	Consult

Options/Accessories

Part #	Description	Price
Summit[®] 3000 Floor Scale		
Consult	Access ramps available	See catalog page 383
Consult	Pit frames available	See catalog page 385
Consult	Bumper guards available	See catalog page 388 through catalog page 390
Consult	Portability frames available	See catalog page 391 through catalog page 394
75819	Floor anchor plates, mild steel (set of two)	Consult
76012	Additional operating manual	Consult
120 Digital Weight Indicator		
76699	Additional operating manual	Consult
19352	RoughDeck floor stand for indicator, 36.3 in high, mild steel	Consult
126384	RoughDeck floor stand for indicator, 48 in high, mild steel	Consult

Summit® Scale and Indicator Package

Floor Scale/120 Plus Indicator Package



Package is configured, corner-trimmed and calibrated for 5,000 divisions before shipping

Floor Scale and Indicator Package

Package includes Summit® 3000 floor scale, 120 Plus digital weight indicator with tilt stand, 20ft load cell cable with quick disconnect; configured and calibrated

Standard Features

Summit® 3000 Floor Scale

- Four NTEP Certified alloy steel-shear beam load cells
- Top access junction box
- Rugged diamond safety treadplate steel deck
- Four adjustable rigid polyurethane rubber feet, 3 in (76.2 mm) diameter
- Signal trim summing board housed in ABS enclosure
- Threaded eyebolt hole (1/2–20NF) located in the center of the deck for easy lifting
- 20 ft of EL147 load cell cable with quick disconnect
- Package configured and calibrated for 5,000 divisions
- Factory-calibrated for 5,000 divisions

120 Plus Digital Weight Indicator

- Large 0.8 in backlit liquid crystal display (LCD)
- 115 or 230 VAC wall adapter with rechargeable battery

Summit 3000 Floor Scale Specifications

End Load Capacity

- 100% full scale at 5,000 lb (2,500 kg)
- 80% full scale at 10,000 lb (5,000 kg)

Cable Length:

- 20 ft (6.1 m) (for connecting junction box to indicator)

Warranty:

- Summit 3000 weldment and load cells two years, all other components one year

Approvals:

- NTEP CC 92-001A9, Class III 5,000 d
- Measurement Canada AM-5530, Class III 5,000 d

120 Plus Digital Weight Indicator Specifications

Power:

- Line voltages: 115 or 230 VAC
- Frequency: 50 or 60 Hz
- Estimated battery life
- 60 hours with 1 x 350 Ω
- 40 hours with 4 x 350 Ω
- Charge time 8 hours

Operating Temperature:

- Legal: 14° F to 104° F (-10° C to 40° C)
- Industrial: 14° F to 122° F (-10° C to 50° C)

Rating/Material:

- Enclosure: heavy gauge ABS

Warranty:

- One-year limited warranty

Approvals:

- NTEP CC 03-059, Class III/IIIL 6,000 d
- Measurement Canada AM 5517
- OIML TC 7626, T5692 5,000 d Class III/IIHHD 6,000 d

Approvals



Summit® Scale and Indicator Package

Floor Scale/Indicator Package

Part Number/Price

Part #	Size (W x L x H)	Capacity	Est. Weight	Price
Floor Scale and Indicator Package (Single Scale)				
Package includes Summit® 3000 floor scale, 120/120 PLUS digital weight indicator with tilt stand, 20 ft load cell cable with quick disconnect; configured and calibrated				
115 VAC				
106913	4 ft x 4 ft x 3.625 in	5,000 lb x 1 lb	315 lb	Consult
106914	4 ft x 4 ft x 3.625 in	10,000 lb x 2 lb	315 lb	Consult
230 VAC				
106915	4 ft x 4 ft x 3.625 in	5,000 lb x 1 lb	315 lb	Consult
106916	4 ft x 4 ft x 3.625 in	10,000 lb x 2 lb	315 lb	Consult
115 VAC Measurement Canada Approved				
106917	4 ft x 4 ft x 3.625 in	2,500 lb x 0.5 kg	315 lb	Consult
106918	4 ft x 4 ft x 3.625 in	5,000 lb x 1 kg	315 lb	Consult

Options/Accessories

Part #	Description	Price
Summit® 3000 Floor Scale		
Consult	Access ramps available	See catalog page 383
Consult	Pit frames available	See catalog page 385
Consult	Bumper guards available	See catalog page 388 through catalog page 390
Consult	Portability frames available	See catalog page 391 through catalog page 394
75819	Floor anchor plates, mild steel (set of two)	Consult
76012	Additional operating manual	Consult
120 Digital Weight Indicator		
103636	Power supply, 120 Plus wall adapter, 115/230 VAC, 5 VDC	Consult
76699	Additional operating manual	Consult
19352	RoughDeck floor stand for indicator, 36.3 in high, mild steel	Consult
126384	RoughDeck floor stand for indicator, 48 in high, mild steel	Consult