

BenchPro™ BP-SR

Shipping Bench Scale with Roller Conveyor

Specifications

Dynamic Response:

Response time for stable weight:
0 - 1,000 d, 1,000 ms, maximum mean average
1,000 d +, 1,500 ms, maximum mean average

Internal Resolution:

500,000 internal count minimum

Overload Protection:

Corner & center overload protection

Power:

In-line power supply (included)
Input: 100-240 VAC, +10% -15%, 3-wire w/ground
Standard terminated with USA 3-prong plug
Output: 12V at .1 Amps DC minimum
Frequency: 50/60 Hz +/-3 Hz, standard
Approvals: UL, CE, EN, CUL

USB HID:

USB 2.0 full speed; Vendor ID: 1C19;
Product ID: 0002

Construction:

Powder coat painted mild steel base plate and load
bridge with stainless steel roller conveyor

Display:

Minimum key press life of 500,000 cycles,
ABS plastic housing
6 annunciators to indicate Zero, Gross/Brutto, Net,
W1/W2/W3 multi-range
4 buttons: Units, Tare, On/Off, F1

RS-232 Cable (included):

10 ft DB 9-pin male to female, straight pass through

USB Cable (included):

46 in (1,168.4 mm) A/B type USB cable

Approvals:

NTEP COC # 17-002
Canada Weights and Measures: AM - 6050
CE Marked

Warranty:

Two-year limited warranty



Standard Features

- Simple operation, easy to set up
- Large six-digit backlight LCD display with 1 in (29 mm) characters protected by heavy duty tempered glass
- Powered USB HID point of sale interface – kg model only
- Nine-pin RS-232 interface for use with SMA and NCI protocols
- Four AA alkaline battery operation for portability
- Gravitational compensation allows for adjustment of factory calibration to meet your local gravity setting, non-approved
- Compatible with FedEx Ship Manager® and UPS Worldship®

APPROVALS



BenchPro™ BP-SR

Shipping Bench Scale with Roller Conveyor

Part Number/Price

Part #	Platform Capacity	Dimensions	Est. Weight	Price
182996	150 x 0.05 lb (75 x 0.02 kg)	12 x 16 in	41 lb	Consult
182394	100 x 0.02 lb (50 x 0.01 kg)	18 x 18 in	77 lb	Consult
182381	150 x 0.05 lb (75 x 0.02 kg)	18 x 18 in	77 lb	Consult
182386	300 x 0.1 lb (150 x 0.05 kg)	18 x 18 in	77 lb	Consult
182398	300 x 0.1 lb (150 x 0.05 kg)	20 x 20 in	94 lb	Consult
182402	300 x 0.1 lb (150 x 0.05 kg)	24 x 24 in	131 lb	Consult

Options/Accessories

Part #	Description	Est. Weight	Price
180901	Second customer display, BenchPro BP-SR no keyboard with 68 in cable	4 lb	Consult
174784	Second remote operator display, BenchPro BP-SR with 68 in cable	4 lb	Consult
183103	16 in (H) tabletop display post for use with second display, customer or remote operator	4 lb	Consult
178501	USB-RS-232 serial adapter	1 lb	Consult

Dimensions - Inches

	A	B	C	D
12 x 16	12	16	15.30	5.95
18 x 18	18	18	21.10	6.50
20 x 20	20	20	23.10	6.50
24 x 24	24	24	27.10	6.50

