Serecknell DCSB Floor Scale Systems

Calibrated with SBI 521 LCD Indicator





This robust DCSB Floor Scale and Indicator System is used for a wide range of general weighing applications where palletized goods are constantly being weighed or moved around by pallet jacks or forklifts. Ideal for most warehouse and shipping areas or where goods need to be consistently weighed.



Accuracy

NTEP at 5000d, Class III



Power

6 volt 4 AH rechargeable internal lead acid battery with 110/220 AC internal transformer



Construction

1/4" / 6 mm thick top plate with heavy duty welded channel support



VALUE IN WEIGHING

Indicator

Comes fully calibrated with the robust stainless steel SBI 521 legal-for-trade indicator



Capacity 5000 lb x 1 lb / 2500 kg x 0.5 kg 10,000 lb x 2 lb / 5000 kg x 1 kg



Display 0.7" / 17 mm LED display

ODDOD Operator Keys

Hold/Setup, Print/Func, N/G/Total, Unit/ Data, Tare/Preset, Zero/On/Off

DCSB Specifications

Deck Construction: Fabricated from high quality carbon steel with a 1/4" / 6 mm hard wearing checker plate top deck structure and specially designed folded channel understructure to help maximize strength where needed

Finish: Powder coat paint

Load Cell: NTEP/OIML approved, IP68 potted 350 ohm +/- 3.5Ω

Load Cell Rated Output: 3mv/V

- J-Box: IP65 ABS junction box with floor scale top access for ease of installation and service
- Interface Cable Length: 15' / 4.5 m with tinned leads (included)

- **Leveling Feet:** Four top access holes for a quick installation
- **Threaded Eye Bolts:** Two threaded top access eyebolt holes for easy mobility and pit service
- Corner Protection: Closed corners to prevent damage to leveling feet

Overload Protection: 150% of rated capacity

Capacity and Resolution:

Model	Capacity	Dimension (in)	Dimension (mm)
DCSB3636-2.5	2500 lb x 0.5 lb 1250 kg x 0.2 kg	36 x 36 x 3.1	914 x 914 x 79
DCSB4848-05	5000 lb x 1 lb 2500 kg x 0.5 kg	48 x 48 x 3.1	1219 x 1219 x 79
DCSB5959-10	10,000 lb x 2 lb 5000 kg x 1 kg	59 x 59 x 3.1	1500 x 1500 x 79

Floor Scale Height Adjustment: min 3.1" / 79 mm; max 4.1" / 104 mm

Certifications: NTEP CC #02-070

Indicator Construction: IP65 heavy duty stainless steel Indicator housing

Display: 0.7" / 17 mm LED display

SBI-521 LED Indicator

- **Operator Keys:** Hold/Setup, Print/Func, N/G/Total, Unit/Data, Tare/Preset, Zero/On/Off
- Functions: Motion, Zero, Net, Gross, Tare, Total, lb, kg, %, pcs, oz, Peak/Hold, HI, OK, LO, AC/CHG

Unit: kg, lb, lb:oz, PCS, %

Display Resolution: Up to 50,000 graduations

Serial Port 1: Full-duplex RS-232

Serial Port 2: Full-duplex RS-232 or half-duplex RS-485

Digital Calibration: Front panel calibration and configuration

Power: 6 volt 4 AH rechargeable internal lead acid battery with 110/220 AC internal transformer

Battery Life: Up to 30 hours in between re-charges

Certifications: NTEP at 5,000d, Class III, CC #11-119

Options

Quick Disconnect Cable: See floor scale price sheet

SBrecknell[®]

brecknellscales.com brecknellscales.co.uk

Part of Avery Weigh-Tronix

Brecknell is part of Avery Weigh-Tronix. Avery Weigh-Tronix is a trademark of Illinois Tool Works group of companies whose ultimate parent company is Illinois Tool Works Inc ("Illinois Tool Works:). Copyright © 2021 Illinois Tool Works. All rights reserved. This publication is issued to provide outline information only and may not be regarded as a representation relating to the products or services concerned. This publication was correct at the time of going to print, however Avery Weigh-Tronix reserves the right to alter without notice the specification, design, price or conditions of supply of any product or service at any time.

DCSBSystemSBI521_L_500114.indd V2 AWT35-500114